********************
ATM Forum Document Number: ATM Forum/95-0809
*******************
Title: Examples of Switch Mechanisms - Corrected Text for the Appendix
********************
Abstract: The example switch scheme in the appendix inadvertantly describes the older time based scheme. It should be replaced by its newer version (ERICA) which is count-based and is compatible with current source requirements. This contribution provides the replacement text.
*******************
Source: Raj Jain is now at
Raj Jain, Shiv Kalyanaraman, and Rohit Goyal The Ohio State University, Department of CIS, Colum Phone: 614-292-3989, Fax: 614-292-2911, Email: Jair  **Mashington University in Saint Loud **Jain@cse.wustl.edu* http://www.cse.wustl.edu/~jain/**
Vijay K. Samalam GTE Laboratories Inc, 40 Sylvan Road, Waltham, MA 02254, Email: vks@gte.ecom
The presentation of this contribution at the ATM Forum is sponsored by NIST.
********************
Date: June 5-9, 1995, Orlando
*******************
Distribution: ATM Forum Technical Working Group Members (Traffic Management)
*******************
Notice: This contribution has been prepared to assist the ATM Forum. It is offered to the Forum as a basis for discussion and is not a binding proposal on the part of any of the contributing organizations. The statements are subject to change in form and content after further study. Specifically, the contributors reserve the right to add to, amend or modify the statements contained herein.
*******************

The appendix section 5.7 in the current draft version of the

traffic management document gives a high level description of the switch mechanisms. While the contributors of that section meant to describe the Explicit Rate Indication for Congestion Avoidance (ERICA) as one of the congestin avoidance mechanisms. He inadvertantly refered to its older version known as OSU scheme, which was time based. The current version ERICA is count based, is compatible with the current source requirements and, therefore, is the correct one to be included. We propose that the subsection entitled "Time-based Congestion Avoidance" be replaced as follows: [Motion]

Explicit Rate Indication For Congestion Avoidance (ERICA)

ERICA [9] tries to maintaion the network at a load z close to one. For this purpose it calculates two quantities fairshare and this VC's share:

Fairshare = Target capacity/Number of active VCs VCshare = CCR / z

Here CCR is the current cell rate declared by the source in the RM cell (or as measured by the switch). This scheme acheives fairness concurrently with efficiency by using the following formula to compute the explicity rate (ER):

ER = Max (Fairshare, VCshare)

The above quantities are measured periodically using information from the forward going RM cells, and the feedback is given in the backward going RM cells. This ensures that the most current information is used to provide fastest feedback. The measurement interval is independent of the rate at which the sources send RM cells. For each interval, no more than one new explicit rate value is advertised per VC. This avoids conflicting feedback to sources due to stale information at the switches. The scheme has few parameters which can be easily tuned. There are a few other variations of this scheme [10].

[9] R. Jain, S. Kalyanaraman, R. Viswanathan, and R. Goyal, "A Sample Switch Algorithm," AF-TM 95-0178R1, February 1995.

[10] R. Jain, S. Kalyanaraman, R. Goyal, "Simulation Results for ERICA Switch Algorithm with VBR+ABR Traffic," ATM Forum/95-0467, April 1995.